

MAGNASOURCE INC.

SAFE-T-ALERT

QUICK REFERENCE GUIDE




| | | Conforms to: | | | | | | | | | | | | | |
|---|-----------------------|--------------|------------|---|-------|------|---------|---|---|----------|---|----------|--|----|---|
| | | | | | | | | | | SAE J994 | | CUL / UL | | CE | |
| | Part # | Voltage | Decibels | Mounting Size | A.A.D | P.P. | S.P.(V) | H | V | U | | | | | |
|  | 1000 SERIES STA10302W | 12-24vdc | 85dB | 2.25"W x 1.5"D x 2.94"H 57MM x 38MM x 75MM | 0.25 | Y | 0.25 | | * | | | | | | * |
| | STA10400W | 12vdc | 92dB | 2.25"W x 1.5"D x 2.94"H 57MM x 38MM x 75MM | 0.35 | Y | 0.35 | | * | | | | | | * |
|  | 2000 SERIES STA20302 | 12-24vdc | 87dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | D | | * | | * | |
| | STA20307 | 12-80vdc | 87dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.725 | | * | D | | * | | * | |
| | STA20502 | 12-24vdc | 97dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA20504 | 12-48vdc | 97dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA20507 | 12-80vdc | 97dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.725 | | * | C | | * | | * | |
| | STA20602 | 12-24vdc | 102dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | | | * | | * | |
| | STA20154A | 12-48vdc | 77-97dB** | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | | | * | | * | |
| | STA20162A | 12-24vdc | 77-102dB** | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | | * | | | * | | * | |
|  | 2100 SERIES STA21502W | 12-24vdc | 97dB | 4.25"W x 1.62"D x 2.74"H 108MM x 41MM x 70MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA21602W | 12-24vdc | 102dB | 4.25"W x 1.62"D x 2.74"H 108MM x 41MM x 70MM | <.6 | Y | -0.25 | | * | | | * | | * | |
|  | 2200 SERIES STA22702W | 12-24vdc | 107dB | 4.25"W x 1.62"D x 2.74"H 108MM x 41MM x 70MM | <.8 | Y | -0.25 | | * | B | | * | | * | |
|  | 2500 SERIES STA25302 | 12-24vdc | 87dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.25 | | * | D | | * | | * | |
| | STA25307 | 12-80vdc | 87dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.725 | | * | D | | * | | * | |
| | STA25502 | 12-24vdc | 97dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA25504 | 12-48vdc | 97dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA25507 | 12-80vdc | 97dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.725 | | * | C | | * | | * | |
| | STA25602 | 12-24vdc | 102dB | 2.62"W x 1.62"D x 3.92"H 67MM x 41MM x 100MM | <.6 | Y | -0.25 | | * | | | * | | * | |
|  | 3200 SERIES STA32502 | 12-24vdc | 97dB | 5"W x 3"D x 2.78"H 127MM x 76MM x 71MM | <.6 | Y | -0.25 | | * | C | | * | | * | |
| | STA32602 | 12-24vdc | 102dB | 5"W x 3"D x 2.78"H 127MM x 76MM x 71MM | <.6 | Y | -0.25 | | * | | | * | | * | |
| | STA32702 | 12-24vdc | 107dB | 5"W x 3"D x 2.78"H 127MM x 76MM x 71MM | <.6 | Y | -0.25 | | * | B | | * | | * | |
| | STA32264A | 12-48vdc | 82-102dB** | 5"W x 3"D x 2.78"H 127MM x 76MM x 71MM | <.6 | Y | -0.25 | | * | | | * | | * | |
|  | 3500 SERIES STA35272A | 12-24vdc | 82-107dB** | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | | | * | | * | |
| | STA35382A | 12-24vdc | 87-112dB** | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | | | * | | * | |
| | STA35582A | 12-24vdc | 97-112dB** | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | | | * | | * | |
| | STA35702 | 12-24vdc | 107dB | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | B | | * | | * | |
| | STA35802 | 12-24vdc | 112dB | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | A | | * | | * | |
| | STA35803 | 12-36vdc | 112dB | 5"W x 4"D x 3.11"H 127MM x 102MM x 79MM | <.8 | Y | -0.25 | | * | A | | * | | * | |
|  | 4000 SERIES STA40802 | 12-24vdc | 112dB | 7.25"W x 4"D x 3.25"H 184MM x 102MM x 83MM | <.8 | Y | -0.25 | | * | | A | * | | * | |
| | STA40582A | 12-24vdc | 97-112dB** | 7.25"W x 4"D x 3.25"H 184MM x 102MM x 83MM | <.8 | Y | -0.25 | | * | | | * | | * | |

** Self adjusting alarms

All SAFE-T-ALERT® Back-Up Alarms are steam cleanable and feature a 2 year warranty

A.A.D. (Average Amp Draw), P.P. (Polarity Protected), S.P.(V) (Spike Protected(V)), Mounting H (Horizontal) V (Vertical) U (Universal)



BACK-UP ALARMS ALARMAS DE RETROCESO AVERTISSEURS DE MARCHE ARRIERE

| | Part # | Voltage | Decibels | Mounting Size | A.A.D | P.P. | S.P.(V) | H | V | U | Conforms to: | | |
|---|------------------------|----------|------------|--|-------|------|---------|---|---|---|--------------|----------|----|
| | | | | | | | | | | | SAE J994 | CUL / UL | CE |
|  | 5000 SERIES STA50154AW | 12-48vdc | 77-97dB** | 4.3"DIA x 1.63"D 109MM x 41MM | <.6 | Y | -0.25 | * | | | * | * | |
| | STA50162AW | 12-24vdc | 77-102dB** | 4.3"DIA x 1.63"D 109MM x 41MM | <.6 | Y | -0.25 | * | | | * | * | |
| | STA50502W | 12-24vdc | 97dB | 4.3"DIA x 1.63"D 109MM x 41MM | <.6 | Y | -0.25 | * | | C | * | * | |
| | STA50602W | 12-24vdc | 102dB | 4.3"DIA x 1.63"D 109MM x 41MM | <.6 | Y | -0.25 | * | | | * | * | |
| | STA50702W | 12-24vdc | 107dB | 4.3"DIA x 1.63"D 109MM x 41MM | <.6 | Y | -0.25 | * | | B | * | * | |
| DUAL FUNCTION  | STA20502DW | 12-24vdc | 97dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | * | | C | * | | |
| | STA20602DW | 12-24vdc | 102dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | * | | | * | | |
| DUAL TONE  | STA20102DT | 12-24vdc | 77dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | * | | | * | | |
| | STA20502DT-G | 12-24vdc | 97dB | 4"W x 1.62"D x 2.73"H 102MM x 41MM x 69MM | <.6 | Y | -0.25 | * | | | * | | |


ALARMS & BELLS ALARMAS Y CAMPANAS DE RETROCESO ALARM & SONNERIES




| | Part # | Voltage | Decibels | Conforms To | | Part # | Voltage | Decibels | Conforms To |
|--|--------|---------|----------|-------------|---|--------|---------|----------|-------------|
| Back-up Alert*  | SY1156 | 12vdc | 87dB | | Alarm  | STA290 | 12vdc | 97dB | |
| | SY3156 | 12vdc | 87dB | | | | | | |
| Motion Alarm  | SYSW01 | 6-28vdc | 68-80dB | UL | Bell  | SY660 | 6" Dia | 87dB | |
| | | | | | | SY861 | 8" Dia | 105dB | |

SWITCHES INTERRUPTORES COMMUTATEURS

| | Part # | Amp Rating | Movement | Conforms To | | Part # | Amp Rating | Movement | Conforms To |
|---|--------|------------|----------|-------------|---|----------|------------|----------|-------------|
|  | SYSW-2 | 5AMP | One Way | |  | SYSWM-43 | 5AMP | 360° | UL |
| | | | | | | | | | |





FLOYD BELL PIEZO ALARMS

| | Part # | Voltage | Decibels | A.A.D. | Mount | Tone |
|---|--------------------|-------------|--------------|---------------------------------|---------------------------------|----------------------------|
| TURBO SERIES  • 2900+/- 250 Hz • Available in 7 different tones: Continuous, Beep, Warble, Siren, Whoop, Staccato & Chime • Available in 2 volume levels and 4 terminations • 1.22" (31mm) Height • 1.41" (36mm) Diameter • Conforms to UL- USA/Canada | SYTMB-V86-201-S(F) | 30-120VAC | 75-95DB+/-5 | 15 mA | Panel Mount | Medium Loud Fast Beep |
| | SYTMB-V86-201-S(S) | 30-120VAC | 75-95DB+/-5 | 15 mA | Panel Mount | Medium Loud Slow Beep |
| | SYTMC-V86-201-S | 30-120VAC | 75-95DB+/-5 | 15 mA | Panel Mount | Medium Loud Continuous |
| | SYTMW-V86-201-S(F) | 30-120VAC | 75-95DB+/-5 | 15 mA | Panel Mount | Medium Loud Fast Warble |
| | SYTMW-V86-201-S(S) | 30-120VAC | 75-95DB+/-5 | 15 mA | Panel Mount | Medium Loud Slow Warble |
| | SYTXB-V86-515-S(F) | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Fast Beep |
| | SYTXB-V86-515-S(S) | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Slow Beep |
| | SYTXC-V86-515-S | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Continuous |
| | SYTXO-V86-515-S | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Whoop |
| | SYTXS-V86-515-S | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Siren Tone |
| | SYTXT-V86-515-S | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Staccato |
| | SYTXW-V86-515-S(F) | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Fast Warble |
| | SYTXW-V86-515-S(S) | 5-15VDC | 92-103DB+/-5 | 50 mA | Panel Mount with Volume Control | Extra Loud Slow Warble |
| | SYTMB-V86-531-S(F) | 5-24VAC/DC | 75-95DB+/-5 | 15 mA | Panel Mount with Volume Control | Medium Loud Fast Beep |
| | SYTMB-V86-531-S(S) | 5-24VAC/DC | 75-95DB+/-5 | 15 mA | Panel Mount with Volume Control | Medium Loud Slow Beep |
| | SYTMC-V86-531-S | 5-24VAC/DC | 75-95DB+/-5 | 15 mA | Panel Mount with Volume Control | Medium Loud Continuous |
| | SYTMW-V86-531-S(F) | 5-24VAC/DC | 75-95DB+/-5 | 15 mA | Panel Mount with Volume Control | Medium Loud Fast Warble |
| | SYTMW-V86-531-S(S) | 5-24VAC/DC | 75-95DB+/-5 | 15 mA | Panel Mount with Volume Control | Medium Loud Slow Warble |
| | SYTCH-V86-530-S(F) | 5-30VDC | 70-90DB+/-5 | 40 mA | Panel Mount with Volume Control | Medium Loud Fast Chime |
| | SYTCH-V86-530-S(M) | 5-30VDC | 75-95DB+/-5 | 40 mA | Panel Mount with Volume Control | Medium Loud Moderate Chime |
| | SYTMB-V86-530-S(F) | 5-30VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Fast Beep |
| | SYTMB-V86-530-S(S) | 5-30VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Slow Beep |
| | SYTMC-V86-530-S | 5-30VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Continuous |
| | SYTMW-V86-530-S(F) | 5-30VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Fast Warble |
| SYTMW-V86-530-S(S) | 5-30VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Slow Warble | |



| | Part # | Voltage | Decibels | A.A.D. | Mount | Tone | |
|--|--------------------|------------|-------------|--------------|---------------------------------|-------------------------|-----------------------------|
|  | SYTMB-V86-948-S(F) | 9-48VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Fast Beep | |
| | SYTMB-V86-948-S(S) | 9-48VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Slow Beep | |
| | SYTMC-V86-948-S | 9-48VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Continuous | |
| | SYTMW-V86-948-S(F) | 9-48VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Fast Warble | |
| | SYTMW-V86-948-S(S) | 9-48VDC | 75-95DB+/-5 | 10 mA | Panel Mount with Volume Control | Medium Loud Slow Warble | |
| AudioLarm II Series | Part # | Height | Voltage | Decibels | A.A.D. | Mount | Tone |
|  | SYMC-07-130-S | 0.96" 24mm | 1-30VDC | 70-93DB+/-5 | 20 mA | Panel Mount | Medium Loud Continuous |
| | SYMC-09-948-S | 1.35" 34mm | 1-48VDC | 85-95DB+/-5 | 20 mA | Panel Mount | Medium Loud Continuous |
| | SYCH-09-525-Q(M) | 1.35" 34mm | 5-25VDC | 70-93DB+/-5 | 25 mA | Panel Mount | Medium Loud Moderate Chime |
| | SYMW-09-530-Q | 1.35" 34mm | 5-30VDC | 85-95DB+/-5 | 20 mA | Panel Mount | Medium Loud Moderate Warble |
| | SYXB-09-630-Q(S) | 1.35" 34mm | 6-30VDC | 85-103DB+/-5 | 50 mA | Panel Mount | Extra Loud Slow Beep |
| <ul style="list-style-type: none"> • 2900+/- 250 Hz • Available in 4 tones: Continuous, Beep, Warble & Chime • 1.41" (36mm) Diameter • Conforms to UL- USA/ Canada | | | | | | | |
| ULTRA Series | Part # | Height | Voltage | Decibels | A.A.D. | Mount | Tone |
|  | SYUC-09-628-Q | 1.35" 34mm | 6-28VDC | 95-108DB+/-5 | 50 mA | Panel Mount | Ultra Loud Continuous |
| <ul style="list-style-type: none"> • 2900+/- 250 Hz • Available in 4 tones: Continuous, Beep, Warble & Chime • 1.41" (36mm) Diameter • Conforms to UL- USA/ Canada | | | | | | | |




WHITE SOUND BROAD BAND BACK UP ALARMA DE RETROCESO DE SONIDO BLANCO ALARME DE RECUIL À LARGE BANDE AVEC "BRUIT BLANC"










- Features Tough, durable, guaranteed waterproof (IP68); Solid-state, spark-free electronics; Epoxy sealed against mud, water & vibration
 - Polarity Protected
 - Multi KHZ Frequency
 - Surge Protection
 - Conforms to SAE J994, CE and 'e' marked (EMC)
 - Operating Temperature: -40 deg C to +85 deg C
- Esta alarma es resistente, duradera y garantizada a prueba de agua (IP68); Estado sólido, libre de chispas; Completamente sellada para protegerla contra el barro, el agua y vibración
 - Protegida contra la polaridad
 - Multi-Frecuencia KHZ
 - Protección contra sobretensiones
 - Cumple con SAE J994, CE y marcada 'E' (EMC)
 - Temperatura de funcionamiento: de -40 °C hasta +85°C
- Imperméabilité garantie (IP68), électronique d'état solide, protégée contre les étincelles, scellée par époxy contre la boue, l'eau et la vibration.
 - Protégée contre la Polarité
 - Multi-fréquence KHZ
 - Protection contre les Surtensions
 - Conforme à SAE J994, CE et marquée 'e' (EMC)
 - Température de Fonctionnement: entre -40 et 85 °C

| | Part # | Description | Vibration | Mechanical Shock | Current |
|---|------------|---------------------------------------|-----------|------------------|---------|
|  | SY82BB | 12-24VDC, 82 dBA | 10G | 100G | .5amp |
| | SY87BB | 12-24VDC, 87 dBA | 10G | 100G | .5amp |
| | SY92BB | 12-24VDC, 92 dB | 10G | 100G | .5amp |
| | SY97BB | 12-24VDC, 97 dB | 10G | 100G | .5amp |
|  | SY97BB-SA | 12-24VDC, 77-97dB SELF ADJUSTING | 10G | 100G | .5amp |
|  | SY87BB-HV | 36-80VDC, 87 dBA | 10G | 100G | .3amp |
| | SY97BB-HV | 36-80VDC, 97 dBA | 10G | 100G | .3amp |
|  | SY102BB | 12-24VDC, 102dBA | 10G | 100G | 1.0amp |
| | SY107BB | 12-24VDC, 107dBA | 10G | 100G | 1.0amp |
| | SY107BB-SA | 12-24VDC, 87-107dBA SELF ADJUSTING | 10G | 100G | 1.0amp |











HORNS BOCINAS KLAXONS

| | Part # | Voltage | Decibels | Size | Warranty | Conforms to |
|--|---------------|----------------|-----------------|-------------------|-----------------|--------------------|
| Light Duty  | SY110 | 36-48vDC | 110dB | 4.25"DIA 108MM | 1 Year | |
| | SY113 | 12vDC | 110dB | 4.25"DIA 108MM | 1 Year | UL |
| | SY115 | 24vDC | 110dB | 4.25"DIA 108MM | 1 Year | UL |
| | SY118 | 72-80vDC | 110dB | 4.25"DIA 108MM | 1 Year | |
| Heavy Duty  | SY100 | 12vDC | 120dB | 5"DIA 127MM | 1 Year | UL |
| | SY101 | 24vDC | 120dB | 5"DIA 127MM | 1 Year | UL |
| | SY103 | 48vDC | 120dB | 5"DIA 127MM | 1 Year | UL |
| | SY105 | 36-48vDC | 120dB | 5"DIA 127MM | 1 Year | UL |
| | SY125 | 36vDC | 120dB | 5"DIA 127MM | 1 Year | |

| | Part # | Voltage | Decibels | Size | Conforms to | Terminals |
|---|---------------|----------------|-----------------|---------------------|--------------------|------------------|
|  | SY102 | 36vDC | 111dB | 5"DIA 127 mm | | 2 |
| | SY106 | 48vDC | 115dB 110dB | 3.4375"DIA 87 mm | | 2 |
|  | SY107 | 12-48vDC | 107dB | 4.625"OD 117 mm | | 2 |
| | SY108 | 12vDC | 116dB | 4"DIA 102 mm | | 1 |
|  | SY109 | 24-48vDC | 116dB | 3.5"DIA 89mm | | 2 |
| | SY111 | 12vDC | 110dB | 4.25"DIA 108mm | | 1 |

| | Part # | Voltage | Decibels | Size | Conforms to | Terminals |
|---|---------|----------|-----------|--------------------|---|-----------|
|  | SY82561 | 12VDC | 104dB | 3.5" DIA 89mm | | 2 |
|  | SY112 | 12VDC | 107dB | 4" DIA 102mm |  | 2 |
|  | SY114 | 24VDC | 104dB | 3.5" DIA 102mm | | 2 |
|  | SY116 | 36-48VDC | 104-114dB | 3.875" DIA 98mm | | 2 |
|  | SY117 | 24VDC | 110dB | 3.5" DIA 89mm | | 2 |
|  | SY119 | 36-48VDC | 105dB | 3.875" DIA 98mm | | 2 |
| | SY120 | 72-80VDC | 105dB | 37/8" DIA 98mm | | 2 |
|  | SY120 | 72-80VDC | 105dB | 37/8" DIA 98mm | | 2 |
|  | SY121 | 12VDC | 110dB | 3 1/2" DIA 89mm | | 2 |

ELECTRONIC HORNS BOCINAS ELECTRÓNICAS KLAXONS ÉLECTRONIQUES

| | Part # | Voltage | Decibels | Size | Conforms To: | Terminals |
|---|-----------|----------|------------|---|---|-----------|
|  | SYE12VLT | 12VDC | 110 dB | 3.6" DIA 143mm | | 2 |
|  | SYE100 | 12VDC | 105-115 dB | 3.5" DIA 89mm |  | 2 |
|  | SYE109 | 24-48VDC | 105-118 dB | 3.5" DIA 89mm |  | 2 |
|  | SYE118 | 72-80VDC | 105-118 dB | 3.5" DIA 89mm |  | |
|  | SY80598 | 12-60VDC | 114 dB | 3.8 x 3.8 x 3.8 DIA 96mm x 96mm x 96mm |  | 2 |
|  | SY82561 | 12VDC | 104 dB | 3.5" DIA | | 2 |
|  | SY88732 | 12VDC | 114 dB | 3.5" DIA | | 3 |
|  | SY88731 | 36VDC | 115 dB | 3.5" DIA | | 3 |
|  | SY1222290 | 12VDC | 115 dB | 2.8" DIA | | 2 |

**** Self adjusting alarms**

All SAFE-T-ALERT® Back-Up Alarms are steam cleanable and feature a 2 year warranty
A.A.D. (Average Amp Draw), P.P. (Polarity Protected), S.P.(V) (Spike Protected(V)), Mounting H (Horizontal) V (Vertical) U (Universal)

| | Part # | Description | | Part # | Description |
|---|----------|----------------------|---|---------|-----------------|
|  | SY107305 | Horn Button Kit |  | SY31420 | Switch Horn Kit |
|  | SY130 | Switch (Universal) |  | SY31664 | Horn Cover |
|  | SY23108 | Switch - Horn |  | SY31829 | Switch - Horn |
|  | SY23198 | Horn Cover |  | SY31976 | Horn Button Kit |
|  | SY23296 | Button - Horn |  | SY34614 | Horn Button Kit |
|  | SY266 | Relay - 12 Volt Horn |  | SY36484 | Button - Horn |
|  | SY28139 | Switch - Horn |  | SY38379 | Plate - Base |
|  | SY29608 | Button - Horn |  | SY39557 | Button - Horn |
|  | SY31231 | Button - Horn |  | SY40224 | Horn Kit |

HORNS, KITS, RELAYS & SWITCHES BOCINAS, KITS, RELÉ Y INTERRUPTORES CLAXONS, JEUX, RELAIS & INTERRUPTEURS

| Part # | Description | Part # | Description |
|---|----------------------|--|----------------------|
| SY41047 | Horn Button Kit | SY47510 | Horn Button Kit |
|  | |  | |
| SY41149 | Horn Button Kit | SY48093 | Horn Relay |
|  | |  | |
| SY41180 | Horn Button Kit | SY54106 | Horn Button Kit |
|  | |  | |
| SY41181 | Horn Button Kit | SY623 | Relay - 12 Volt Horn |
|  | |  | |
| SY41561 | Relay - 12 Volt Horn | SY73008 | Cover - Horn Button |
|  | |  | |
| SY42634 | Switch | SY77807 | Button - Horn |
|  | |  | |
| SY42675 | Horn Button Kit | SY88351 | Switch - Horn |
|  | |  | |
| SY44012 | Switch Horn Button | SY88352 | Switch - Horn |
|  | |  | |
| SY44888 | Cap Assembly | SY88540 | Switch - Horn Button |
|  | |  | |

| | Part # | Description | | Part # | Description |
|---|---------|-----------------|--|---------|-----------------|
|  | SY88541 | Horn Cover |  | SY88549 | Button - Horn |
|  | SY88542 | Horn Button Kit |  | SY88550 | Button - Horn |
|  | SY88543 | Button - Horn |  | SY88551 | Button - Horn |
|  | SY88544 | Cap |  | SY88552 | Horn Button Kit |
|  | SY88545 | Horn Button |  | SY88553 | Cup - Horn Kit |
|  | SY88547 | Button - Horn |  | SY88554 | Button - Horn |
|  | SY88548 | Button - Horn |  | SYMS105 | Switch |

MAGNASOURCE_{INC.}

833-362-8590 / support@magnasourceinc.com
WWW.MAGNASOURCEINC.COM